

## 4-CH H.265 VIDEO ENCODER, RUGGED

### FEATURES



- Real-time digital transmission of HD/SD full motion imagery
- H.265 HEVC / H.264 AVC
- SD/HD/3G-SDI or Composite Video Input Interface
- 1080p/1080i/720p/480i/576i
- Primary/Secondary Video Encoding
- TS/UDP and RTSP/RTP/UDP Protocols
- MPEG-2 compliant TS multiplexing
- Synchronous Serial or Ethernet TS Interfaces
- 10/100/1000 network interface
- Data Rates from 64Kbps to 20Mbps
- <50ms Encode Latency
- Stereo/dual-channel audio inputs per channel
- MPEG-1 Layer II Audio Compression
- Metadata Support
  - ◆ Synchronous VANC
  - ◆ Serial
  - ◆ Ethernet
  - ◆ KLV Encoding
- MISB/STANAG Compliant
- IRIG-B/1PPS Time Input
- Serial or Ethernet port configurable
- Rugged, MIL Qualified Package

The Model 7840R 4-Channel H.265 Video Encoder is an HD/SD video encoder that compresses video and audio signals, multiplexing them with metadata and other system information for real-time video transmission applications. The 7840R is capable of simultaneously encoding four channels of video with resolutions up to 1080p. Utilizing the H.265 (HEVC) video compression algorithm, the encoder provides high quality video transmission at various resolutions and a wide range of bandwidths. The H.265 compression algorithm utilizes highly bit-efficient coding to provide encoded streams at nearly half the bandwidth of its H.264 (AVC) predecessor. The unit is built on an advanced, low-power multimedia architecture that provides the horsepower for the computationally intensive H.265 algorithm, providing bandwidth efficiency for multi-channel applications. This increased efficiency allows for more channels to be transmitted over a given bandwidth, better quality video for constrained bandwidth applications, or lower bandwidth operation to extend the limits of ISR operation and reduce storage size requirements. The 7840R also provides an H.264 mode to support legacy infrastructures while providing a future growth path to H.265.

Designed for any rugged airborne, ground-mobile, or shipboard application, the 7840R is compliant with the full motion video standards developed by the US Government's Motion Imagery Standards Board (MISB). This includes compliance with the video compression, KLV metadata, and transport stream profiles required to ensure interoperability in US and Allied processing, dissemination, and exploitation (PED) systems. Full MIL-STD-810 environmental and MIL-STD-461/DO-160 EMI qualification ensures the 7840R meets project requirements.

The 7840R is easily integrated into any FMV system, providing for legacy composite and all SDI standards. The unit provides Ethernet and synchronous serial transport interfaces along with multi-format metadata interfaces. Serial or Telnet control, and an easy to use web-GUI are provided for encoder set-up.

TECHNICAL SPECIFICATIONS

# MODEL 7840R

## 4-CH H.265 VIDEO ENCODER, RUGGED

### VIDEO INPUT

**Ports** 4 independent inputs  
**Format** SD/HD-SDI (SMPTE) or Composite (2x) , Auto-detect format, resolution, frame rate  
**Levels** .3Vp-p; 75 Ohms/1Vp-p, 75 Ohms

### VIDEO COMPRESSION

**Algorithm** H.265 HEVC / H.264 AVC  
**Profile** CBP, MP, M10P / BP, MP, HP  
**Resolutions** 1080p/1080i/720p/480i/576i  
**Frame Rate** 1-60  
**GOP Structure** Inter/Intra; Variable Size

### TRANSPORT STREAM

**Ports** Ethernet or RS-422  
**Protocol** ISO/IEC 13818-1  
MPEG-2 Transport Stream containing Video/Audio/Data  
**Data Rate** 64Kbps - 20Mbps  
**Ethernet Protocol** Transport Stream over UDP, unicast or multicast  
RTSP/RTP over UDP  
**RS-422 Protocol** Transport Stream over synchronous serial interface

### ETHERNET INTERFACE

**Format** 10/100/1000 Base-T, Auto Sense Bitrate, Auto Detect Full Duplex  
**Configuration** DHCP or Static Address

### METADATA INTERFACE

**Ports** Asynchronous serial, UDP, SDI-VANC (4)  
**Format** KLV or unformatted data

### TIME INTERFACE

**Ports** 1PPS/IRIG-B, SDI-VANC  
**1PPS Levels** 0-10Vp-p; 50 Ohms

### CONTROL

**Ports** Asynchronous Serial, Telnet/SSH, Web Browser (HTTP/HTTPS)  
**Serial Levels** RS-232/RS-422

### AUDIO INPUT

**Ports** Two independent stereo inputs  
**Format** Balanced (Line Level)  
**Levels** 2.8Vp-p (1Vrms)  
**Impedance** 10K Ohms

### AUDIO COMPRESSION

**Channels** None, Left, Right, Stereo  
**Algorithm** MPEG-1 Layer I/II or ADPCM  
**Sample Rates** 48Ksps

### LATENCY

**Encoder** <50ms (per channel)

### ENVIRONMENTAL (MIL-STD-810F)

**Temp/High** 501.4/Table 501.4-II +71°C  
**Temp/Low** 501.4 - 55°C  
**Humidity** 507.4 Proc II: 11-day Aggravated  
**Vibration** 514.5 Category 13 Figure 514.5C-9  
**Mechanical Shock** DO-160 Section 7 Category A 6G/11ms  
**Altitude** 500.4 Proc I/II -2,000Ft to +50,000Ft  
**Alt Rapid Decomp** 500.4 Proc III 8,000Ft to 50,000Ft in 15s

### EMI

**MIL-STD-461E** CS101, CS114-116, RS103, RE102, CE-102

### POWER

**Volts** +28VDC (IAW MIL-STD-704/1275)  
**Watts** <20W

### SIZE / WEIGHT

**Chassis** 2.62"H x 5.0"W x 7.06"D / 3.75lbs  
66.55mm x 127.0mm x 179.32mm/1.7Kg



©2021 Delta Information Systems, Inc.  
All rights reserved. Revision 2 020421

A division of Delta Information Systems, Inc.

747 Dresher Road, Suite 125 • Horsham, PA 19044-2247 • Tel (215) 657-5270 • Fax (215) 657-5273 • [www.deltadigitalvideo.com](http://www.deltadigitalvideo.com)